

TRINCIA CON ATTACCO A 3 PUNTI 118/TL PER TRATTORI FLAIL MOWER WHIT 3 POINT ATTACK 118/TL



 Trincia utilizzato in oliveti, frutteti, parchi e giardini per la frantumazione di erbacce, rovi stocchi di mais, potatura di olivi e viti ecc...; adattabile a trattori muniti di attacco a 3 punti fisso. Scatola rinvio ad angolo in ghisa con ruota libera a bagno d'olio. Coltelli in acciaio forgiato di spessore mm. 6, ancorati con bulloni diam. 16 e dadi autobloccanti. Cinghie trapezoidali rinforzate e dentellate. Rullo regolazione altezza lavoro bombato alle estremità. Struttura in lamiera rinforzata.

 Flail mower for mulching weeds, brushwood, corn stubbles, pruning residuals from olive trees, etc. in olive groves, orchards, vineyards, parks and gardens. The flail mower has to be mounted to tractors with fix 3-point hitch. The cast iron angular gear box with oil bath includes a free wheel hub. The fish tail flails in forged steel have a thickness of 6 mm and are mounted to the electronically balanced rotor by 16 mm diameter bolts with self-locking nuts. Reinforced toothed v-belts guarantee excellent power transmission. The rear roller is adjustable in height and has curved ends for better lateral sliding. Structure is made out of reinforced sheet metal.

SPECIFICHE TECNICHE - TECHNICAL PROPERTIES

MODELLO MODEL	LARGHEZZA LAVORO WORKING WIDTH CM.	INGOMBRO CM. DIMENSIONS WIDTH	POTENZA MINIMA RICHIESTA REQUEST MINIMUM POWER		COLTELLI FLAILS	PESO Kg WEIGHT Kg	
118/TL 100	100	110	16 cv	12 kw	32	145	
118/TL 120	120	130	20,5 cv	15 kw	40	170	
118/TL 140	140	150	33 cv	24 kw	44	180	

TRINCIA CON SPOSTAMENTO LATERALE 118/TLSM-SI FLAIL MOWER WITH SIDE SHIFTING 118/TLSM-SI



Trincia utilizzato in oliveti, frutteti, parchi e giardini per la frantumazione di erbacce, rovi stocchi di mais, potatura di olivi e viti ecc...; adattabile a trattori muniti di attacco a 3 punti con spostamento manuale (SM) o idraulico (SI). Scatola rinvio ad angolo in ghisa con ruota libera a bagno d'olio. Coltelli in acciaio forgiato di spessore mm. 6, ancorati con bulloni diam. 16 e dadi autobloccanti. Cinghie trapezoidali rinforzate e dentellate. Rullo regolazione altezza lavoro bombato alle estremità. Struttura in lamiera rinforzata.



Flail mower for mulching weeds, brushwood, corn stubbles, pruning residuals from olive trees, etc. in olive groves, orchards, vineyards, parks and gardens. The flail mower has to be mounted to tractors with 3-point hitch and can be either with manual (SM) or hydraulic (SI) lateral offset. The cast iron angular gear box with oil bath includes a free wheel hub. The fish tail flails in forged steel have a thickness of 6 mm and are mounted to the electronically balanced rotor by 16 mm diameter bolts with self-locking nuts. Reinforced toothed v-belts guarantee excellent power transmission. The rear roller is adjustable in height and has curved ends for better lateral sliding. Structure is made out of reinforced sheet metal.

SPECIFICHE TECNICHE - TECHNICAL PROPERTIES

MODELLO MODEL	LARGHEZZA LAVORO WORKING WIDTH CM.	INGOMBRO CM. DIMENSIONS WIDTH	POTENZA MINIMA RICHIESTA REQUEST MINIMUM POWER		COLTELLI FLAILS	PESO Kg WEIGHT Kg		
118/TLM-TLI 100	100	110	16 cv	12 kw	32	175	38	70
118/TLM-TLI 120	120	130	20,5 cv	15 kw	40	200	50	90
118/TLM-TLI 140	140	150	33 cv	24 kw	44	210	70	110